CREATIVE LAB

บริษัท ครีเอทีฟแล็บ เชียวใหม่ จำกัด **CREATOR**

RGB FLEXIBLE STRIP

Features

- Cover with silicone tube for waterproof (IP65)

and without silicone for non waterproof (IP20), Thickness(Double) PCB

- High lumen 22 Lm/LED, Low power consumption 14.4 W/M.
- Easy to install by 3M Glue, Silicone, Clamp lock or Fix in Aluminium Profile

Applications

- Used for building decoration both for indoor and outdoor, can be used with many type

of Aluminium Profile Fitting (If needed Aluminium Profile)

- Long life time, easy to use

Product Group	14
Product Name	Flexible Strip 5050 60led
Code	14-017
Description	Flexible Strip 5050 60led
Model of Fitting	White PCB 10 mm.
Light Source	EPISTAR Chip 5050 SMD 60 LED/M
Dimension (mm) (W x L)	10 x 5000
Input Voltage (VDC)	12V
Input Current (A)	1.2A
Power Consumption (W)	14.4W
Luminous Flux (LM) & CRI	22 LM/LED (1,320 LM/M), CRI≥85
Beam Angle	120 °
Control	Option of DMX or simple color changing controller
Mounting Detail	Clamp Lock, 3M Glue, Silicone or Aluminium Profile
Available Color	RGB

ສົດຕ່ອ : 053-235526 ,061-6545249 creativelab_cm@hotmail.co.th Brighten up Your Business with High Quality LED



5050SMD



