

CREATIVE LAB

บริษัท ครีเอทีฟแล็บ เซียนใหม่ จำกัด



Ribbon 2835 120led 12V

ติดต่อ : 053-235526 ,061-6545249
creativelab_cm@hotmail.co.th
Brighten up Your Business
with High Quality LED

Features

- Cover with silicone tube for waterproof (IP65) and without silicone for non waterproof (IP20), Thickness(Double) PCB
- High lumen 26 Lm/LED, Low power consumption 4.8 W/M.
- Easy to install by 3M Glue, Silicone, Clamp lock or Fix in Aluminium Profile

Applications

- Used for building decoration both for indoor and outdoor, can be used with many type of Aluminium Profile Fitting (If needed Aluminium Profile)
- Long life time, easy to use



2835SMD

Product Group	14
Product Name	Ribbon 2835 120led 12V
Code	14-161
Description	Ribbon 2835 120led 12V
Model of Fitting	White PCB 8 mm.
Dimension (mm) (W x L)	8 x 5000
Input Voltage (VDC)	12V
Input Current (A)	0.40A
Power Consumption (W)	4.8W
Luminous Flux (LM) & CRI	26 LM/LED (3,120LM/M), CRI \geq 85
Beam Angle	120 °
Control	External Switching Power Supply
Mounting Detail	Clamp Lock, 3M Glue, Silicone or Aluminium Profile
Available Color	Warm White (2,800-3,200K)

