CREATIVE LAB

บริษัท ครีเอทีฟแล็บ เชียวใหม่ จำกัด **CREATOR**

Ribbon 5050 120led 24V 1Line LED

Features

- Cover with silicone tube for waterproof (IP65)

and without silicone for non waterproof (IP20), Thickness(Double) PCB

- High lumen 26 Lm/LED, Low power consumption 28.8 W/M.

- Easy to install by 3M Glue, Silicone, Clamp lock or Fix in Aluminium Profile

Applications

- Used for building decoration both for indoor and outdoor, can be used with many type

- of Aluminium Profile Fitting (If needed Aluminium Profile)
- Long life time, easy to use



5050SMD

Product Group	14
Product Name	Ribbon 5050 120led 24V 1Line LED
Code	14-163
Description	Ribbon 5050 120led 24V 1Line LED
Model of Fitting	White PCB 10 mm.
Dimension (mm) (W x L)	10 x 5000
Input Voltage (VDC)	24V
Input Current (A)	1.20A
Power Consumption (W)	28.8W
Luminous Flux (LM) & CRI	26 LM/LED (3,120LM/M), CRI≥85
Beam Angle	120 °
Control	External Switching Power Supply
Mounting Detail	Clamp Lock, 3M Glue, Silicone or Aluminium Profile
Available Color	Cool White (4,000-4,500K)



ຕົດຕ່ອ : 053-235526 ,061-6545249 creativelab_cm@hotmail.co.th Brighten up Your Business with High Quality LED