

CREATIVE LAB

บริษัท ครีเอทีฟแล็บ เซียนใหม่ จำกัด



ติดต่อ : 053-235526 ,061-6545249

creativelab_cm@hotmail.co.th

Brighten up Your Business
with High Quality LED

Ribbon 5050 60led

Features

- Cover with silicone tube for waterproof (IP65) and without silicone for non waterproof (IP20), Thickness(Double) PCB
- High lumen 26 Lm/LED, Low power consumption 14.4 W/M.
- Easy to install by 3M Glue, Silicone, Clamp lock or Fix in Aluminium Profile

Applications

- Used for building decoration both for indoor and outdoor, can be used with many type of Aluminium Profile Fitting (If needed Aluminium Profile)
- Long life time, easy to use



5050SMD

Product Group	14
Product Name	Flexible Strip 5050 60led
Code	-
Description	Flexible Strip 5050 60led
Model of Fitting	White PCB 10 mm.
Light Source	EPISTAR Chip 5050 SMD 60 LED/M
Dimension (mm) (W x L)	12 x 5000
Input Voltage (VDC)	24V
Input Current (A)	0.6A
Power Consumption (W)	14.4W
Luminous Flux (LM) & CRI	26 LM/LED (Max 1,560LM/M), CRI \geq 85
Beam Angle	120 °
Control	External Switching Power Supply
Mounting Detail	Clamp Lock, 3M Glue, Silicone or Aluminium Profile
Available Color	Nature White (4,000-4,500K)

